		RN 32-125 2P/ 2900 [rpm] 1Stage							Curve N. <b>T-1319</b>																	
ax.diameter 1 [mm]		Min						n.diameter 3 [mm]						Suction Ø 50 [mm]						Discharge Ø 32 [mm]						
nsity 1 and v	/iscos	ity 1 cS												Replace any previous edition						V= [mm]						
													•													
ŀ	Head	l ;	1		-	_	:	1	1			:	:	1	1	ı	1		:			1 1	;	1		
7								_				ļ														
22.0					ļ					$\sim$	\									; ;						
22.0_		ļ	ļ		ļ																					
_			ļ ļ	ļ ļ	-  -		ļ	ļ ļ		 							ļ								-	
20.0_																									-	
-			ļ	ļ ļ	 			ļ ļ	<u> </u>	 		ļ								 						
1		·	ļ				ļ	ļ	ļ			ļ	ļ				·			L						
18.0_					<u> </u>		$\overline{}$	_						1												
1							ļ			\												    				
16.0		ļ	ļ	ļ	ļ		ļ			¦			ļ							 -					-	
-					ļ															\					-	
1									T												<u></u>		<u> </u>			
14.0_		+							1						_						/			\ 0. ~	404	
‡		+	·		<del></del>				1	 			÷					 		 		/		∖s ø	H3 T	
40.0			ļ	ļ	-  -		_		<u>.</u>			; ;	ļ ļ	-	ļ ļ										-	
12.0_																				 			/		-	
			ļ		 				i											; ;						
10.0_																				/				VA Ø	130	
Ĭ							<u>.</u>		ļ												<u></u>					
+		ļ	ļ	ļ	ļ		ļ					}	ļ		·						/	D Ø118			-	
8.0_		-			1		-		1				-	1								1 1	-		-	
1							}		·											 						
6.0			; ;	\	 		{ {	 	÷	¦		; ;	÷				1	Ø10	3	¦		 				
	)			1	F 0	•	1		1	10.0	<b>•</b>	1	1	1	15.0	•				20.0				25.0	•	
m³/h] 0.0					5.0	,				10.0	,				15.0	,				20.0				25.0	J	
1.50_ <del>p</del>	Powe	er								!										!				s ø a ø	131	
1				ļ 	 		ļ L	ļ 1	ļ	ļ Ļ		ļ	ļ 		ļ ļ								<u></u>	_A Ø	130	
+		·}	ļ	ļ	ļ		ļ					ļ		<del></del>			Ť								-	
1.00_	)	-							-			<del></del>		-								D Ø118				
1		·	; ;	( : ( :	-  -  <u>-</u>				<del></del>	F	·····			<del></del>	<del></del>					} }		 				
1				-		_			<u> </u>		Ī	ļ		j	 			. O.10	2			ļ <u>-</u>				
0.50_			<u> </u>		<del></del>				-			-	-	-	-			Ø10	J	-		1		-		
‡					+			ļ	ļ	ļ		ļ								ļ					1	
1		·	ļ Ļ	ļ	 		ļ		÷	 		ļ Ļ			ļ					 					-	
/] 0.00_	-	1			1				1					i								į į				
6.0_ <mark>0</mark>	NPSI	Hr	1		1				1			,		1								1 2		βØ	130	
5.0_			<u> </u>						; ; ;			<u> </u>											/	<b>/</b>	]	
∄	)		<u> </u>						†														/			
4.0	)		<u> </u>	<u></u>					i	<u> </u>		<u> </u>						<u> </u>		<u> </u>						
3.0_		-	<u> </u>	<u> </u>					‡				-	<u> </u>				<u> </u>								
∄	,		<u> </u>	<u> </u>	<u> </u>		<u> </u>	:	<u> </u>		<u> </u>	; <del></del>	<u> </u>	<u> </u>		1								=======================================		
2.0	· · · · · ·	ļ	;		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,									<del></del>			×									
1.0_	· · · · · · ·		}																						-	
·																										
nments			0==:		_																					
00rpm m user	near	s 2P(			erforr	nanc	NS NS	ould	chan	geac	sss	ingto	o the			rspe	ed	Ιn	ate				Ro	vision		
			Impeller				22	22				14			Author				Date Mar28,2019				1,6	Revision		