		1	RN 450 [Stag	rpm]		-00	4P	/		Curve N. T-1363													
Max.diameter		. Juage					n.diame 7 [mn		· ·	Suction Ø 125 [mm]						Discharge Ø 100 [mm]							
ensity 1 and		ity 1 c	2+			34	<i>i</i> [iiiii	ניין					Replace any previous edition				נווווון						
ensity i and	VISCUS	oity i Co	οι									Re	ріасе апу рі	evious edilic	л								
60.0_	Head	i																					
60.0_	•	1	1	1	1				1 1	T	1			1	1			1	1	1	1		
					1]]			
			.ļ	ļ						<u> </u>	; ;			ļ				ļ :	ļ	į			
	-	.}	- !															ļ :	ļ				
55.0_	•	1	1	1	1				1					1	-			1	1	1			
	†		÷	-j -										1					-j ·				
	Ī										,												
	1								ļ 		- 												
50.0_	—				_	_		_										-		-			
	+																						
	†								!		_			1									
	I]						\setminus											
45.0_	\downarrow	-	1	1	1										-			-	1	-			
	+		ļ										· · · · · · · · · · · · · · · · · · ·					A Ø4	105	ļ			
	1	<u> </u>				<u> </u>			ļ														
	1		 	j	3	1			<u> </u>					1	×			}	j	filler:	[]		
40.0_			1	1	1														-	1			
	Į	·		ļ	ļ				}}		<u>.</u>	ļ		ļ				ļ	ļ				
	 	-}	·}	ļ												· · · / · · · ·		ļ	ļ	ļ			
	†	·	·	÷	1						} !					/				†			
35.0_	1			-j	1				† 														
00.0	Ĭ								ļ									D 0	, , , , , , , , , , , , , , , , , , ,	ļ			
	-	-}	}	ļ	<u> </u>				<u> </u>									B Ø3	3//				
	ļ	· 	·}	ļ	į				·					· · · / ·	·					į			
30.0_	†										! ! !		 		<u>_</u> :								
30.0	Î					J								J									
	ļ				i				ļ 		! !									i			
	4								+		: : :			ļ									
n] 25.0_	+								1		! !					\C_k	347						
	•			1		φ			1	•			· · · · ·	Φ			φ	+	1	1	•		
[m³/h] 0.0		er			50.0)			100.0	0			150.0)		200.0)				250.0		
40.00_	Ŷ								ļ					Ii				A Ø4	10E				
	<u> </u>	. 		 					† 		; ;				· · · · · · · ·			A 104	+05	ļ			
30.00_	ļ		÷						ļ									B Ø3	377				
	Ĭ			ļ	<u> </u>				<u> </u>											j			
	<u> </u>		ļ	<u> </u>	<u> </u>	1	ļ <u>ļ</u>							1		C	347	ļ	j	<u> </u>			
20.00	b	1	1	1	1									-	-			-	1	1			
	7		<u> </u>							+								ļ	\	}			
10.00_	 			+		<u></u>			ļ <u></u>		[£	ļ	ļ			
10.00_	-		-			ļ			<u> </u>									ļ		ļ			
			·			1	[i							1						ļ			
kW] 0.00_																		i					
	•																						
0.0	NPS	Hr																					
6.U_	Ŷ				ļ				ļļ											ļ			
	<u> </u>	. j	ļ	ļ Ļ	ļ	1			ļļ			<u> </u>		1			/	A Ø4	105	j			
6.0_	1	<u> </u>	<u> </u>	<u> </u>	<u> </u>				<u> </u>										<u> </u>	<u> </u>			
	Ť	ļ	ļ- -	<u> </u>	<u> </u>	ļ			1 1								1	ļ	ļ	<u> </u>			
	7	·	·	ļ					† †		,												
4.0_	ļ					1			·					1									
	‡	. 		-j -j		1							 				ļ			į			
	<u> </u>					1			1														
m] 2.0_	6	1		1	1	1																	
Comments			_	_					_		_		_										
	mear	ns 4P@50Hz. Performa				manc																	
Diffuser			Impe	eller			NS 47			SSS			Author			Date	0			Revis	sion		
			1			17				118						Apr 2, 201	J			1			