		RN 125-400 4P/ 1450 [rpm] 1Stage												Curve N. T-1367 Suction Ø Discharge Ø																					
Max.diamete		Min.diameter 364 [mm]											150							50 [mm]							Disch								
Density 1 and	visco	sity ′	cSt															R	deplace any previous edition																
	Ноо	ч																																	
60.0_	P -	- 		-1-			<u></u>	<u> </u>	+-								1									Ī		1 1							
-															-	_	-	_																	
-								-	-											_	_							;; 							
55.0_							 	 	 	.					ļ			ļ	ļ						<u> </u>							<u> </u>			
-																						ļ						 							
50.0_	F -						-	Ţ	 				_	_													\								
50.0_	•							ļ	1	ļ					ļ	<u> </u>	_	$\overline{}$																	
-									-		<u> </u>						ļ	ļ		_								 	\setminus						
45.0_							<u>.</u>	<u>:</u>							ļ		ļ	ļ						ļ											
43.0_							<u> </u>	ļ					-		-		<u> </u>		ļ			ļ										<u></u>			
-	1							1			1				}		-	\	\			ļ	\					- -					AQ	405	
40.0_	1						<u> </u>	1			Ŀij				<u> </u>	ļ	<u> </u>	<u> </u>	<u> </u>			<u> </u>			<u>-</u>	ļ									
-	-																																		
-	1;							1							ļ									\					\setminus						
35.0_															}				}						/					/					
-										-}							ļ										/				/				
-	ļ						i	1	‡	- - 					} }		ļ	 	; ;			 	 					\setminus					ВΩ	380	
30.0_								†···	<u> </u>	·																		>	/						
-	Ĭ						i				ļį						j	i 				j	: 		L					\					
-	1							Į	Ţ	·}					ļ				ļ					ļ							/				
25.0_								1	1																							\ \			
-	1						ļ		<u> </u>	·}	li				}		ļ	 	ļ			ļ		}			 					\	C	364	
-										-}							ļ	ļ	ļ			ļ													
[m] 20.0_					-	,	i	+	†**	+	•											 	 			•		;; 		-		+			
[m³/h] 0.0	o [']			50	0.0				1	00.0)			1	50.0	,			2	00.0				2	50.0	,			300	.0			3	50.0	
60.00_	Pow	er								,																									
-	Ĭ						i	<u> </u>	<u> </u>	- 					} } }		ļ 1	Suction Ø 150 [mm] Replace any previous edition			 						ΑQ) 405							
50.00_	•							1	1																					+-	 -				
-								<u> </u>	-						ļ		ļ					 			•		 						В	380	
40.00_																		<u> </u>	-	 -													C-Q	3364	
30.00_								7																									£		
-							<u></u>	<u>.</u>		<u> </u>								 -							ļ ļ										
20.00_									-							1						ļ:													
-				 			-:	7							<u> </u>													 							
[kW]10.00_	<u>_</u> _								+		<u> </u> -														ļ										
8.0_	NPS	SHr														1																	A 6	3405	
-	‡																					ļ			L			<u>-</u> -				/	````		
6.0_							 		÷	-} - <u>}</u>					} }		{·		ļ	}		{	 		<u>-</u>		{	 -			/			† 	
0.0_											lj				ļ ļ		ļ	ļ 	ļ			 		ļ	<u>-</u>			 					ļ		
- - 	1						i								} }		ļ						\			ļ ļ,							ļ		
4.0_	•							<u> </u>																-	\times										
-	‡														ļ			-i		 			-		 										
[m] 2.0_	1		:				:	1	-1		1										1					1									
Comments 1450rpm r	mea	ns 4	.P@∙	50H	z. F	Per	for	ma	nce	s co	ulde	ha	ทตร	ac	cor	din	a to	the	rea	lm	oto	rsn	eed	1					-		_				_
Diffuser		Impeller							NS					SSS		<u></u>		Author						Date						Re	Revision				
										19					138										ŀ	Jan	28,2	2011							