		RN 40-160 1450 [rpm] 1Stage				4P/			Curve N. <b>T-1377</b>																
lax.diameter 67 [mm]						Min.diameter 137 [mm]				Suction Ø <b>65 [mm]</b>								Discharge Ø 40 [mm]							
ensity 1 and vis	scosity 1 c	:St			ο, <sub>[</sub>							Replace any previous edition						40 [111111]							
10.0_ <del>0</del>	ead	1 1		-	,				-		-		1		-		-	,		1					
+-					ļ		1						 												
Ţ.					$\overline{}$	_													[			ļ			
9.0			-		ļ		-					-	! !						ļ			ļ			
9.0					<u></u>	<u> </u>	<u> </u>											1	L	<u> </u>		<u> </u>			
4-			-		. <del>.</del>						-								ļ			ļ			
+-			-		·						-	····													
8.0													_												
+-					j		·							<u> </u>					}			÷			
1.					$\overline{}$																				
7.0			-		ļ	· <del> </del>									-/				ļ						
7.0_					<u>.</u>		1									<b>\</b>		1	L			İ			
4-						· <del> </del>	į			$\searrow$						->	<u> </u>		ļ			ļ			
1					 . 1	4	1			 	/		 				/		ļ				 		
6.0	1 1		-	_		+	1		- 1	+	+-				+	+	+	1	1	1		1			
+-					_	\	<u> </u>					<u> </u>		<del> </del>				1	ļ			ļ 	 		
1.														\					1						
5.0					ļ		į		\	<del></del>	·			/			·		/	<u> </u>		ļ	<del>  </del>		
1.5					ļ										/					/					
+			-													<u></u>				· `	<b>\</b>	ļ			
1.																									
4.0	1 1	- : :			1	1	1	1	- 1	-	1	-			-			1	1	1	<u> </u>	$\overline{}$	1 1		
1:			-		1	1	1											×	1						
4.			-		ļ	·								_/				- \	ļ			ļ`	ΑØ	107	
3.0			-												/:				/						
1.					ļ	. <del> </del>										<b>\</b>			-7	B Ø	1151	ļ			
+-			-		ļ							-								VD X	, 131	ļ			
1:																	/C (	Ø137	ļ			ļ			
] 2.0	<del>- i - i</del>	<del>- i - i</del>	•		-	1	<del> </del> (	<del>-</del>	-	-	+	•			-	<b>-</b>	-	i	1	1	<del> </del>	1	<del>i i</del>	-	
[m³/h] 0.0			5.0				10.0				15.0	)			20	.0				25.0	)				30.0
0.60_P	ower				J		1																		
₹:																							ΑØ	167	
0.50																_									
<u> </u>					J		<u> </u>												ļ					:::::	
0.40							<del></del>	4												B-0	151				
<u> </u>					3														1				53	5	
0.30					<u> </u>		<del> </del>										С	<b>Ø</b> 137							
<u></u> f:		اب	_  -			<u> </u>	1				+														
0.20			_  -				<u></u>				+														
‡	;		_  -		j							1	, 						[			·			
V] 0.10		- 7					ļ				+								1						
J																									
	DO: :																								
8.0 N	P5Hr						1																Λα	167	
<u> </u>					3	1																	ΑØ	107	
6.0							ļ													÷		Ţ			
#:					-		<u> </u>				4			<del>-</del>								ļ	;;;; <u>;</u>		
4.0							1																		
#:					3	1										-			1			ļ	53	3	
2.0					-	-							$\rightarrow$												
#:						1	1																		
0.0																			1						
Ź																									
mments																									
50rpm me	ans 4P	@50Hz.	Perf	forman			ldch	ange			g to t	he re	al m	otors	peed	ı									
fuser		Impeller				NS			SS	SS			Author					Date <b>Apr 1, 2019</b>					Revision		
					2	22			51								Α	pr1,	201	9					