	14	RN 40-250 4P/ 1450 [rpm] 1 Stage								Curve N. T-1379														
Max.diameter 51 [mm]						∕lin.diam 27 [m							Suct	tion ! mn	Ø nl				4	Discharge 0 [mm]	Ø			
ensity 1 and visco	osity 1 cS	St				[,			65 [mm] Replace any previous edit					us editi	ion								
25.0 Hea	ad	1 1		-		-		1 1				1	1 1		- 1	1 1	-		1 1				!	
+			-																					
+	-						+																	
ļ	 	- -	- -					1		_								1						
20.0			-																					
	ļļ																							
	-						<u></u>	ļļ							<u> </u>		ζ							
		-																						
15.0				-								-			-								1	
+																	\sim	/						
+	 																	1	<u> </u>					
+															<u></u>			/	/					
10.0							1				1							/						
											-													
ļ		-1														\	\			\A	Ø251	L		
																	/			\				
																		\		__				
5.0				+							-				-	1 1				В	Ø247			
0.0	÷																		\c -ø2	27				
m³/h] 0.0			5.0			10.	0			15.0			2	0.0			25.	0		30.0			35.0	
2.50 Pow	ver																	.1		:				
																				A	Ø251			
2.00	1											 								В	Ø247			
1.50														-										
<u> </u>	ļ <u>-</u>						<u> </u>	1	-										_C Ø2	27				
1.00				_ 	-			-																
0.50	+							i i					}}											
J		-						 																
v] 0.00																								
8.0_NPS	SHr																							
	ļ																				Ø251			
6.0	1							1											1000		2201			
	11							1																
4.0	1																							
2.0	13	-																	Z					
	<u> </u>						-						×			+	<u>-</u>							
0.0		-						1																
mments 50rpm mea	ns 4P	<u>-</u> მ50I	-lz P	erfo	rman	Ces co		chang	le ac	cor	dinat	o the	real	mc	otoren	heed								
fuser		Impeller				nces could change a				SSS				Author				Date				Revis	on	
						11		11										Jan31,2011						