	14	RN 50-125 4F 1450 [rpm] 1Stage					T-1859												
Max.diamete		Mi 12						Suction Ø 65 [mm]				Discharge Ø 50 [mm]							
Density 1 and	viscosity 1 cS	št		l l							Replace any previous edition								
7.0	Head •				<u> </u>		<u> </u>		1			I	1 1						
-				+ + - +							-	1							
6.0																			
-	Īii						:												
-		1	- -																
5.0_	•			1 1									\backslash		\rightarrow				
-		- + +	- + +	++.			<u> </u>												
4.0_																			
-						 												\s ø1	51
-						 	}					1							
3.0	•			-11				1 1	1				<u> </u>				\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	A Ø1	46
-											 					\D Ø13	36		
2.0																		1 1 1	
-																			
-												1		\				1	
1.0								1 1											
-							! !									\F Ø12	24		
[m] 0.0 _—																			
[m³/h] 0.0		5.0		10.0	o '	1	15.0		20.0)	25	.0		30.0		35.0)	40	.0
0.60_	Power										ļ <u>i i</u>			.				S Ø1	51
0.50_																		A Ø1	46
0.40																_D Ø1:	36	; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	
0.40								-					 			- 		1	
0.30_						-			1							_F Ø12	24		<u></u>
0.20_			4	4-1-															
[kW] 0.10_																			
[]	0																		
2.0_	NPSHr			! !	!	! !	: 1	1 1	1 !	!	!!!!		1 1	: 1		1 1	1 !	1 1 1	
-							 				 		ļļ.						
-	<u> </u>					 	{		· 		}	1					-	s Ø1	51
1.0 _—	ļ						1					1	1	*					
-																			
[m] 0.0																			
Comments																			
	neans 4P(@50Hz.Performanco			es coul	d char	nge a	sss	cording to the real			peed		Date				Revision	
Sindooi		ппревег			36			135	135			Author			Apr 1, 2019				